

*Amended*  
*Amended*  
detector/analyser and output means are used to receive radiation scattered at said sensing location.

*Amended*  
*B2*  
7. (Amended) A method according to Claim 1 wherein the radiation source and input means are operated to direct radiation towards said sensing location and the detector/analyser and output means are used to receive radiation transmitted through said sensing location.

*Amended*  
*B2*  
8. (Amended) A method according to Claim 1 wherein the radiation source and input means are operated to direct radiation towards said sensing location and the detector/analyser and output means are used to receive radiation emitted from said sensing location.

*Amended*  
*B2*  
9. (Amended) A method according to Claim 1 including a step of examining the spectroscopic characteristics of the radiation received by the detector/analyser to provide data relating to the chemical nature of liquid at the sensing location.

*Amended*  
*B2*  
10. (Amended) A method according to claim 1 wherein the radiation source and detector/analyser are remote from the site and are connected to the input and output means, respectively, via waveguide means.

*Amended*  
*B2*  
11. (Amended) A method according to claim 1 wherein there are a plurality of sensor assemblies which are located at different sites, and the method includes switching the connection of the radiation source and/or the detector/analyser between different sensor assemblies.

*Amended*  
*B2*  
14. (Amended) An assembly according to Claim 10 wherein the detector/analyser comprises means for spectroscopic analysis.

*Amended*  
*B2*  
15. (Amended) An assembly according to Claim 12 further comprising a vessel containing a hydrophobic liquid and wherein said hydrophobic element is located at a site